

AUTOMATIC COOKTOP FIRE SUPPRESSION

STOVETOP FIRESTOP MICROHOOD[®] SPECIFICATIONS

INTENDED USE	Indoor, residential stovetop grease fires (<i>not more than 3/8" oil depth</i>)
ACTIVATION METHOD	Automatic when there is direct, sustained contact with a flame
POWDER DISPERSAL METHOD	Gravity (non-pressurized)
PRIMARY SUPPRESSION AGENT	Non-Toxic dry powder
INTENDED APPLICATION	Microwave oven overhead, or other lower vent hoods or cabinets
REQUIRED VERTICAL CLEARANCE	15-27" between the underside of the microwave and the cooking surface
REQUIRED HORIZONTAL DISTANCE FROM BACK WALL	Should be at least 14" from back wall (back of stove) to lower front edge of microwave oven door
WEIGHT—TOTAL PRODUCT (OUNCES)	30 oz. (per housing)
WEIGHT—POWDER (OUNCES)	Approximately 5.2 oz. (per canister)/Each pair contains four canisters
HEIGHT (INCHES)	2.2"
LENGTH (INCHES)	13.9" (including mounting bracket)
WIDTH (INCHES)	3.9"
INSTALLATION METHOD	Drywall anchors and screws (included) hold device to back wall, positioned below the microwave *Extension bars available upon request
NUMBER OF DEVICES NEEDED TO COVER A 4-BURNER STOVETOP	Two (one pair)
TESTS PERFORMED	Device and dry powder tested by an independent nationally recognized testing laboratory (NRTL)
EFFECTIVE LIFE	6 years, replace upon activation or before "remove or replace before" date found on label

