AUTOMATIC COOKTOP FIRE SUPPRESSION



RETURN PACKAGING INSTRUCTIONS

If your original packaging materials are unavailable, follow these instructions to return your StoveTop FireStop® Automatic Fire Suppressors.

Returns by Corrugated Box

- 1. Use a corrugated box with an established weight rating.
- 2. Use less than 75 percent of the weight capacity of the box. Each StoveTop FireStop canister weighs approximately 12 ounces.
- 3. Line the corrugated box with a plastic material to prevent spillage in the event a StoveTop FireStop canister is broken. A standard trash bag—approximately 1.2 mil thick—should suffice.
- 4. Fill the box with StoveTop FireStop canisters by placing each canister on its side (label), end to end (lid to lid).
- 5. Once you fill the box, fill any remaining voids with packaging material (such as Styrofoam peanuts), and seal the box closed with standard packaging tape. Seal all exposed corners and edges with tape to prevent potential spillage.

StoveTop FireStop is U.S. DOT exempt; therefore, no special labeling (other than the address) or further packaging are required.

Returns by Barrel

- 1. Use a plastic or metal shipping barrel with an established weight rating.
- 2. Use less than the weight capacity of the barrel. (Each StoveTop FireStop canister weighs approximately 12 ounces.) For volume reference only, approximately 120 StoveTop FireStop canisters will fit into a 30-gallon barrel.
- 3. Fill the box with StoveTop FireStop canisters by placing each canister on its side (label), end to end (lid to lid).
- 4. Once you fill the barrel, properly secure the barrel to prevent spillage. No special labeling or further packaging are required.

Address Units To: Williams-Pyro, Inc. Disposal 200 Greenleaf Street Fort Worth, Texas 76107

