



STOVETOP FIRESTOP


RANGEHOOD 675-3D




 The Original Canister-Based Fire Suppressor

 Simple, magnet-based installation

 One pair protects a typical residential, 4-burner stove

 No maintenance or inspections needed


 6-year effective life



Deploys automatically when the flame from a cooking fire comes in direct, sustained contact with the fuse


MOUNTING HEIGHT


27 - 35 INCHES





STFS PLUS 679-3A





 Omnidirectional ramp for broader coverage of the cooking surface

 Simple, magnet-based installation

 Modern appearance


 One pair protects a typical residential, 4-burner stove

 No maintenance or inspections needed

 6-year effective life




Deploys automatically when the flame from a cooking fire comes in direct, sustained contact with the fuse

 Additional powder capacity


MOUNTING HEIGHT


15 - 32 INCHES





MICROHOOD 677-1 | 677-2





 Designed to mount under microwaves or low cabinets over the stove

 One pair protects a typical residential, 4-burner stove

 Alternative mounting options available

 No maintenance or inspections needed

 Color options: Black or White


 6-year effective life



Deploys automatically when the flame from a cooking fire comes in direct, sustained contact with the fuse


MOUNTING HEIGHT


15 - 27 INCHES





PLUS LC 679-LC-3A





 ClickBar® for easy installation under microwaves and other low clearance situations

 Omnidirectional ramp for broader coverage of the cooking surface

 Modern appearance


 One pair protects a typical residential, 4-burner stove

 No maintenance or inspections needed

 6-year effective life



Deploys automatically when the flame from a cooking fire comes in direct, sustained contact with the fuse

 Additional powder capacity

MOUNTING HEIGHT

15 - 32 INCHES

